

MODEL	Screen Size	75"	86"
PANEL	Panel Technology	TFT LCD	TFT LCD
	Display Resolution	3840 x 2160	3840 x 2160
	Brightness (Typical)	400 cd / m ²	400 cd / m ²
	Contrast (Typical)	1200:1 (BOE)	4000:1 (AUO)
	Response Time (Gray To Gray)	8 ms	8 ms
	Frame Rate	60 Hz	60 Hz
	Viewing Angle (H / V)	178° / 178°	178° / 178°
	Backlight Type	Direct LED	Direct LED
	Service Life(Typical)	50,000 Hours	50,000 Hours
	Low Blue Light(hardware)	Yes	Yes
	NTSC	72%	72%
Installation	Landscape	Landscape	
TOUCH	Detection Method	Infrared	Infrared
	Available Touch Point	50 Point (10point Φ2mm)	50 Point (10point Φ2mm)
	Response Time (Typical)	<=3.3ms	<=3.3ms
	Minimum Response Size	>=2.5mm	>=2.5mm
	Ink In Tools	Yes	Yes
	Scan Rate	≥300Hz	≥300Hz
	Touch Resolution	32768 x 32768	32768 x 32768
	Communication Interface	USB+USB	USB+USB
CONNECTIVITY (SA# Mainboard)	USB 2.0	1(Side/Type-A)	1(Side/Type-A)
	USB Type C (Android USB 2.0 OTG)	1 (Side)	1 (Side)
	TF-Card	1 (Side)	1 (Side)
	HDMI IN 2.0	1 (Side/Type-A)	1 (Side/Type-B)
	Touch out	1 (Side/Type-B)	1 (Side/Type-A)
	HDMI OUT 2.0	1 (Side/Type-A)	1 (Side/Type-B)
	LAN	1 (Side ; RJ45 for 1000M/100M/10M Ethernet)	1 (Side ; RJ45 for 1000M/100M/10M Ethernet)
	S/PDIF OUT	1 (Bottom)	1 (Bottom)
	RS232	1 (Bottom)	1 (Bottom)
	Earphone	1 (Bottom)	1 (Bottom)
	MIC In	1 (Bottom)	1 (Bottom)
	WI-Fi Module(Build in)	1x 802.11 ax	1x 802.11 ax
	Bluetooth	V 5.4	V 5.4
CONNECTIVITY (Front Interface Board)	USB Type C (USB 2.0)	1	1
	HDMI IN 2.0	1	1
	Touch out	1 (Type-B)	1 (Type-B)
	USB3.0	1 (Type-A)	1 (Type-A)
	USB2.0	1 (Type-A)	1 (Type-A)
CONNECTIVITY (OPS board)	OPS Slot	1(Intel Spec 80Pin)	1(Intel Spec 80Pin)
SOUND	Audio Power Output	15W x 2	15W x 2
	Speaker Position	Forward	Forward
Mic-array	Mic-array	8-array	8-array
Camera	Camera (Built-in)	48M	13M
SMART SYSTEM	Main Board	RK3576	RK3576
	CPU	Quad Cortex-A72 and Quad Cortex-A53	Quad Cortex-A72 and Quad Cortex-A53
	GPU	ARM Mali G52 MC3	ARM Mali G52 MC3
	Operating System	Android 16.0	Android 16.0
	RAM	8GB	8GB
POWER	Internal Storage	128GB	128GB
	Power Supply	AC 100-240 V 50 / 60Hz	AC 100-240 V 50 / 60Hz
	Power Consumption (in Operation)	TBD	TBD
MECHANICAL	Power Consumption (in Standby)	<= 0.5 W	<= 0.5 W
	Appearance ID	6J	6J
	Front Glass	Tempered Glass (Anti-glare/Spray)	Tempered Glass (Anti-glare/Spray)
	Aluminum Frame	Black	Black
	Pen Holder	Yes	Yes
	Buttons	7 Buttons (Power/Source/return/Home/Setting/Vol-/Vol+)	7 Buttons (Power/Source/return/Home/Setting/Vol-/Vol+)
	Dimension of Product (W x H x D)	TBD	TBD
	Dimension of Package Carton (W x H x D)	TBD	TBD
	VESA® Hole Pitch (W x H)	TBD	TBD
	Weight of Product	TBD	TBD
	Weight of Package Carton (Gross)	TBD	TBD
ACCESSORIES	Container Loads-20	TBD	TBD
	Container Loads-40H	TBD	TBD
ENVIRONMENTAL	Accessories	-	-
	Operation Temperature	5 - 35 °C	5 - 35 °C
	Storage Temperature	-15 - 45 °C	-15 - 45 °C
	Operation Humidity	20 - 80 %RH (No Condensation)	20 - 80 %RH (No Condensation)
Storage Humidity	<=80 %RH	<=80 %RH	