

MODEL	Screen Size	65"	75"	86"
PANEL	Panel Technology	TFT LCD	TFT LCD	TFT LCD
	Display Resolution	3840 x 2160	3840 x 2160	3840 x 2160
	Brightness (Typical)	300 cd / m <sup>2</sup>	300 cd / m <sup>2</sup>	300 cd / m <sup>2</sup>
	Contrast (Typical)	4000 : 1(AUO)	1200 : 1(BOE)	4000 : 1(AUO)
	Response Time (Gray To Gray)	8 ms	8 ms	8 ms
	Frame Rate	60 Hz	60 Hz	60 Hz
	Viewing Angle (H / V)	178° / 178°	178° / 178°	178° / 178°
	Backlight Type	Direct LED	Direct LED	Direct LED
	Service Life	> 30,000 Hours	> 30,000 Hours	> 30,000 Hours
	NTSC	72%	72%	72%
Installation	Landscape	Landscape	Landscape	
TOUCH	Detection Method	Infrared		
	Available Touch Point	50 Point (5point Φ3mm)		
	Response Time (Typical)	<=5ms		
	Minimum Response Size	>=3mm		
	Ink In Tools	Yes		
	Scan Rate	≥200Hz		
	Touch Resolution	32768 x 32768		
Communication Interface	USB			
CONNECTIVITY (SR# Mainboard)	USB 2.0	2 (Side/Type-A)	2 (Side/Type-A)	2 (Side/Type-A)
	TF card	1(Side)	1(Side)	1(Side)
	TOUCH OUT	1 (Side/USB Type-B 2.0)	1 (Side/USB Type-B 2.0)	1 (Side/USB Type-B 2.0)
	HDMI IN 2.0	1 (Side/Type-A)	1 (Side/Type-A)	1 (Side/Type-A)
	RS-232C	1 (Side/DB-9F)	1 (Side/DB-9F)	1 (Side/DB-9F)
	MIC IN	1 ( Side/3.5mm)	1 ( Side/3.5mm)	1 ( Side/3.5mm)
	Earphone	1 (Side/3.5mm)	1 (Side/3.5mm)	1 (Side/3.5mm)
	S/PDIF	1 (Side/coaxial)	1 (Side/coaxial)	1 (Side/coaxial)
	LAN	1 ( Side/RJ45 for 10/100M)	1 ( Side/RJ45 for 10/100M)	1 ( Side/RJ45 for 10/100M)
	Wi-Fi Module	1x 802.11 ax	1x 802.11 ax	1x 802.11 ax
Bluetooth	V5.4	V5.4	V5.4	
CONNECTIVITY (Front Interface Board)	USB C	1(Front/type-C ,USB 2.0 only)	1(Front/type-C ,USB 2.0 only)	1(Front/type-C ,USB 2.0 only)
	HDMI IN 2.0	1 (Front/Type-A)	1 (Front/Type-A)	1 (Front/Type-A)
	TOUCH OUT	1(Front/type-A ,USB 3.0)	1(Front/type-A ,USB 3.0)	1(Front/type-A ,USB 3.0)
	USB 3.0	2 (Front/Type-A)	2 (Front/Type-A)	2 (Front/Type-A)
CONNECTIVITY (OPS board)	OPS slot	1(Intel Spec 80Pin)	1(Intel Spec 80Pin)	1(Intel Spec 80Pin)
Mic-array	Mic-array	8-array	8-array	8-array
Camera	Camera (Built-in)	48M	48M	48M
SOUND	Audio Power Output	15W x 2	15W x 2	15W x 2
	Subwoofer	N/A	N/A	N/A
	Speaker Position	Down Firing	Down Firing	Down Firing
ADDITIONAL	light sensor	Yes	Yes	Yes
	Human body induction	Yes	Yes	Yes
SMART SYSTEM	Main Board	V610	V610	V610
	CPU	ARM Cortex A55x8	ARM Cortex A55x8	ARM Cortex A55x8
	GPU	Mali-G52MC	Mali-G52MC	Mali-G52MC
	Operating System	Android 15.0	Android 15.0	Android 15.0
	RAM	4 GB	4 GB	4 GB
	Internal Storage	32 GB	32 GB	32 GB
POWER	Power Supply	AC 200-260 V 50 / 60Hz 5.5A	AC 200-260 V 50 / 60Hz 5.5A	AC 200-260 V 50 / 60Hz 5.5A
	Power Consumption (in Operation)	TBD	TBD	TBD
	Power Consumption (in Standby)	<= 0.5 W	<= 0.5 W	<= 0.5 W
MECHANICAL	Appearance ID	6A	6A	6A
	Front Glass	Tempered Glass (Anti-glare/coating)	Tempered Glass (Anti-glare/coating)	Tempered Glass (Anti-glare/coating)
	Aluminum Frame	Black	Black	Black
	Buttons	1 Button(Power)	1 Button(Power)	1 Button(Power)
	Dimension of Product (W x H x D)	TBD	TBD	TBD
	Dimension of Package Carton (W x H x D)	TBD	TBD	TBD
	VESA® Hole Pitch (W x H)	400 x 600 (mm), M8 Screw	800 x 600 (mm), M8 Screw	800 x 600 (mm), M8 Screw
	Weight of Product Kg	TBD	TBD	TBD
	Weight of Package Carton (Gross) Kg	TBD	TBD	TBD
	Container Loads-20	76	36	32
Container Loads-40H	168	152	66	
ACCESSORIES	Accessories	-	-	-
ENVIRONMENTAL	Operation Temperature	5 - 35 °C	5 - 35 °C	5 - 35 °C
	Storage Temperature	-15 - 45 °C	-15 - 45 °C	-15 - 45 °C
	Operation Humidity	20 - 80 %RH (No Condensation)	20 - 80 %RH (No Condensation)	20 - 80 %RH (No Condensation)
	Storage Humidity	<=80 %RH	<=80 %RH	<=80 %RH