

MODEL		43	55"	65"	75"	86"
PANEL	Screen Size	43"	55"	65"	75"	86"
	Panel Technology	TFT LCD	TFT LCD	TFT LCD	TFT LCD	TFT LCD
	Display Resolution	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160
	Brightness (Type)	500 cd / m <sup>2</sup>	500 cd / m <sup>2</sup>	500 cd / m <sup>2</sup>	500 cd / m <sup>2</sup>	500 cd / m <sup>2</sup>
	Contrast (Type)	4000 : 1	1200 : 1	5000 : 1	1200 : 1	4000 : 1
	Response Time (Gray To Gray)	8 ms	8 ms	8 ms	8 ms	8 ms
	Frame Rate	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz
	Viewing Angle (H / V)	178° / 178°	178° / 178°	178° / 178°	178° / 178°	178° / 178°
	Backlight Type	Direct LED	Direct LED	Direct LED	Direct LED	Direct LED
	Service Life	> 30,000 Hours	> 30,000 Hours	> 30,000 Hours	> 30,000 Hours	> 30,000 Hours
Installation	Landscape&Portrait	Landscape&Portrait	Landscape&Portrait	Landscape&Portrait	Landscape&Portrait	
CONNECTIVITY	HDMI2.0 Inputs	1(Side)	1(Side)	1(Side)	1(Side)	1(Side)
	HDMI Out	1(Side)	1(Side)	1(Side)	1(Side)	1(Side)
	DC in	N/A	N/A	N/A	N/A	N/A
	Android USB 2.0	1 (Type-C/Side)	1 (Type-C/Side)	1 (Type-C/Side)	1 (Type-C/Side)	1 (Type-C/Side)
	Android USB 3.0	2(Type-A/Side)	2(Type-A/Side)	2(Type-A/Side)	2(Type-A/Side)	2(Type-A/Side)
	Line out	1 ( Mini Jack/Side)	1 ( Mini Jack/Side)	1 ( Mini Jack/Side)	1 ( Mini Jack/Side)	1 ( Mini Jack/Side)
	TF Card	1 (Micro/Side)	1 (Micro/Side)	1 (Micro/Side)	1 (Micro/Side)	1 (Micro/Side)
	LAN	1 (1000M/Side)	1 (1000M/Side)	1 (1000M/Side)	1 (1000M/Side)	1 (1000M/Side)
WiFi Module	1X 802.11 ax	1X 802.11 ax	1X 802.11 ax	1X 802.11 ax	1X 802.11 ax	
SOUND	Audio Power Output (RMS)	8W x 2	8W x 2	8W x 2	8W x 2	8W x 2
	Subwoofer	N/A	N/A	N/A	N/A	N/A
	Speaker Position	Back Firing	Back Firing	Back Firing	Back Firing	Back Firing
	Sound Mode	Standard	Standard	Standard	Standard	Standard
SMART SYSTEM	Main Board	RK3576	RK3576	RK3576	RK3576	RK3576
	CPU	Quad core Cortex-A72 and quad core Cortex-	Quad core Cortex-A72 and quad core Cortex-	Quad core Cortex-A72 and quad core Cortex-	Quad core Cortex-A72 and quad core Cortex-	Quad core Cortex-A72 and quad core Cortex-
	GPU	ARM Mali G52 MC3	ARM Mali G52 MC3	ARM Mali G52 MC3	ARM Mali G52 MC3	ARM Mali G52 MC3
	Operating System	Android 14.0	Android 14.0	Android 14.0	Android 14.0	Android 14.0

	Memory	4 GB	4 GB	4 GB	4 GB	4 GB
	On-Board Storage	32 GB	32 GB	32 GB	32 GB	32 GB
<b>OSD</b>	OSD Language Function	English	English	English	English	English
<b>MECHANICAL</b>	Appearance ID	23#	23#	23#	23#	23#
	Button	1	1	1	1	1
	Dimension of Product (W x H x D)	960X66X553 mm	1234X62X705 mm	1454 X62X829 mm	1693X75X971mm	1937X75X1109mm
	Dimension of Package Carton (W x H x D)	1069X155X671 mm	1376X190X846 mm	1593X190X967mm	1839X190X1127mm	2084x190x1264mm
	VESA® Hole Pitch (W x H)	400 x 400 (mm), M8 Screw	400 x 400 (mm), M8 Screw	400 x 400 (mm), M8 Screw	800 x 600 (mm), M8 Screw	800 x 600 (mm), M8 Screw
	Weight of Product	TBD	TBD	21.5Kg	TBD	TBD
	Weight of Package Carton (Gross)	TBD	TBD	30Kg	TBD	TBD
	Container Loads-20	TBD	TBD	TBD	TBD	TBD
	Container Loads-40H	TBD	TBD	TBD	TBD	TBD
<b>POWER</b>	Power Supply	AC 100-240 V 50 / 60Hz	AC 100-240 V 50 / 60Hz	AC 100-240 V 50 / 60Hz	AC 100-240 V 50 / 60Hz	AC 100-240 V 50 / 60Hz
	Power Consumption (in Operation)	TBD	TBD	TBD	TBD	TBD
	Power Consumption (in Standby)	<= 0.5 W	<= 0.5 W	<= 0.5 W	<= 0.5 W	<= 0.5 W
	ECO Sensor	N/A	N/A	N/A	N/A	N/A
	Energy Label Rating		N/A	N/A	N/A	N/A
<b>ENVIRONMENTAL</b>	Operation Temperature	5 - 35 °C	5 - 35 °C	5 - 35 °C	5 - 35 °C	5 - 35 °C
	Storage Temperature	-15 - 45 °C	-15 - 45 °C	-15 - 45 °C	-15 - 45 °C	-15 - 45 °C
	Operation Humidity	20 - 80 %RH (No Condensation)	20 - 80 %RH (No Condensation)	20 - 80 %RH (No Condensation)	20 - 80 %RH (No Condensation)	20 - 80 %RH (No Condensation)
	Storage Humidity	<=80 %RH	<=80 %RH	<=80 %RH	<=80 %RH	<=80 %RH