

MODEL	Screen Size	65"	75"	86"
PANEL	Panel Technology	TFT LCD	TFT LCD	TFT LCD
	Display Resolution	3840 x 2160	3840 x 2160	3840 x 2160
	Brightness (Type)	400 cd / m²	400 cd / m²	400 cd / m²
	Contrast (Type)	4000 : 1 (AUO)	1200 : 1 (BOE)	4000 : 1 (AUO)
	Response Time (Gray To Gray)	8 ms	8 ms	8 ms
	Frame Rate	60 Hz	60 Hz	60 Hz
	Viewing Angle (H / V)	178° / 178°	178° / 178°	178° / 178°
	Backlight Type	Direct LED	Direct LED	Direct LED
	Service Life	> 30,000 Hours	> 30,000 Hours	> 30,000 Hours
	Installation	Landscape	Landscape	Landscape
TOUCH	Detection Method	Infrared	Infrared	Infrared
	Available Touch Point	50 Point (10 point Φ2.5mm)	50 Point (10 point Φ2.5mm)	50 Point (10 point Φ2.5mm)
	Response Time (Type)	≤5ms	≤5ms	≤5ms
	Minimum Response Size	≥2.5mm	≥2.5mm	≥2.5mm
	Scan Rate	≥200hz	≥200hz	≥200hz
	Touch Resolution	32768 x 32768	32768 x 32768	32768 x 32768
	Communication Interface	USB	USB	USB
CONNECTIVITY	HDMI2.1 Input(s)	2(Side)	2(Side)	2(Side)
	USB 2.0Port(s)	2 (Side/ Type-A)	2 (Side/ Type-A)	2 (Side/ Type-A)
	DisplayPort 1.2Input(s)	1(Side)	1(Side)	1(Side)
	LAN (rj45)	1(Side)	1(Side)	1(Side)
	RS-232C Port(s)	1 (Side/DB-9F)	1 (Side/DB-9F)	1 (Side/DB-9F)
	Touch out	1 (Side/USB Type-B 2.0)	1 (Side/USB Type-B 2.0)	1 (Side/USB Type-B 2.0)
	USB Type C	1 (Type-C/DP1.2+15W+TOUCH USB)	1 (Type-C/DP1.2+15W+TOUCH USB)	1 (Type-C/DP1.2+15W+TOUCH USB)
CONNECTIVITY (OPS board)	Audio Out	1(Side/Mini Jack)	1(Side/Mini Jack)	1(Side/Mini Jack)
	OPS Slot	Yes	Yes	Yes
SOUND	Audio Power Output (RMS)	15W x 2	15W x 2	15W x 2
	Subwoofer	N/A	N/A	N/A
	Speaker Position	Bottom	Bottom	Bottom
	Sound Mode	Standard/News/Music/Movie/Sports/User	Standard/News/Music/Movie/Sports/User	Standard/News/Music/Movie/Sports/User
OSD	OSD	English	English	English
SMART SYSTEM	CPU	-	-	-
	GPU	-	-	-
	Operating System	-	-	-
	Memory	-	-	-

	On-Board Storage	-	-	-
MECHANICAL	Appearance ID	6C	6C	6C
	Dimension of Product (W x H x D)	1490x878x84mm	1701x992x84mm	1946.4x1130.3x97mm
	Dimension of Package Carton (W x H x D)	1615x1000x190mm	1839x1127x190mm	2084x1264x190mm
	VESA® Hole Pitch (W x H)	600 x 400 (mm), M8 Screw	800 x 600 (mm), M8 Screw	800 x 600 (mm), M8 Screw
	Weight of Product	37kg	49kg	59kg
	Weight of Package Carton (Gross)	48kg	64kg	75kg
	Container Loads-20	76(With Pallet)	36(With Pallet)	32(With Pallet)
	Container Loads-40H	172(With Pallet)	152(With Pallet)	66(With Pallet)
	Front Glass	Tempered Glass (Spray/Anti-glare Type/3mm)	Tempered Glass (Spray/Anti-glare Type/3mm)	Tempered Glass (Spray/Anti-glare Type/3mm)
ACCESSORIES	Touch pen	2pcs	2pcs	2pcs
	Power cable	1pcs (3m)	1pcs (3m)	1pcs (3m)
	Remote control	1pcs	1pcs	1pcs
	Wall mount	Optional	Optional	Optional
POWER	Power Supply	AC 100-240 V 50 / 60Hz	AC 100-240 V 50 / 60Hz	AC 100-240 V 50 / 60Hz
	Power Consumption (in Operation)	TBD	TBD	TBD
	Power Consumption (in Standby)	≤ 0.5 W	≤ 0.5 W	≤ 0.5 W
	Light Sensor	Yes	Yes	Yes
ENVIRONMENTAL	Operation Temperature	5 - 35 °C	5 - 35 °C	5 - 35 °C
	Storage Temperature	-15 - 45 °C	-15 - 45 °C	-15 - 45 °C
	Operation Humidity	20 - 80 %RH (No Condensation)	20 - 80 %RH (No Condensation)	20 - 80 %RH (No Condensation)
	Storage Humidity	≤80 %RH	≤80 %RH	≤80 %RH

