MODEL	Screen Size	86''
PANEL	Panel Technology	TFT LCD
	Display Resolution	3840 x 2160
	Brightness (Typical)	300 cd / ㎡
	Contrast (Typical)	1200 : 1(BOE)
	Response Time (Gray To Gray)	8 ms
	Frame Rate	60 Hz
	Viewing Angle (H / V)	178° / 178°
	Backlight Type	Direct LED
	Service Life	> 30,000 Hours
	NTSC	72%
	Installation	Landscape
TOUCH	Detection Method	P-CAP Bonded
	Avalilable Touch Point	40 Points
	Response Time (Typical)	<=10 ms
	Minimum Response Size	-
	Ink In Tools	N/A
	Scan Rate	>=100 Hz
	Touch Resolution	-
	Communication Interface	USB
CONNECTIVITY （SR# Mainboard）	USB 2.0	2 (Side/Type-A)
	TF card	1(Side)
	TOUCH OUT	1 (Side/USB Type-B 2.0)
	HDMI IN 2.0	1 (Side/Type-A)
	RS-232C	1 (Side/DB-9F)
	Mic In	1 (Side/3.5mm)
	Earphone	1 (Side/3.5mm)
	S/PDIF	1 (Side/coaxial）
	LAN	1 (Side/RJ45 for 10/100M)
	Wi-Fi Module	1x 802.11 ax
	Bluttooth	V5.4
CONNECTIVITY （Front Interface Board）	USB C	1(Front/type-C ,USB 2.0 only)
	HDMI IN 2.0	1 (Front/Type-A)
	TOUCH OUT	1(Front/type-A ,USB 3.0)
	USB 3.0	2 (Front/Type-A)
CONNECTIVITY (OPS board)	OPS slot	1(Intel Spec 80Pin)
Mic-array	Mic-array	8-array
Camera	Camera (Built-in)	48M
SOUND	Audio Power Output	15W x 2
	Subwoofer	N/A
	Speaker Position	Down Firing
ADDITIONAL	light sensor	Yes
	Human body induction	Yes
SMART SYSTEM	Main Board	V660
	CPU	ARM Cortex A55x8
	GPU	Mali-G52MC
	Operating System	Android 15.0
	RAM	4 GB
	Internal Storage	32 GB
POWER	Power Supply	AC 200-260 V 50 / 60Hz 5.5A
	Power Consumption (in Operation)	TBD
	Power Consumption (in Standby)	<= 0.5 W
MECHANICAL	Appearance ID	25
	Front Glass	Tempered Glass (Anti-glare/coating)
	Aluminum Frame	Black
	Buttons	1 Button(Power)
	Dimension of Product (W x H x D)	TBD
	Dimension of Package Carton (W x H x D)	TBD
	VESA® Hole Pitch (W x H)	N/A
	Weight of Product Kg	TBD
	Weight of Package Carton (Gross) Kg	TBD

	Container Loads-20	20
	Container Loads-40H	41
ACCESSORIES	**Accessories**	-
ENVIRONMENTAL	**Operation Temperature**	5 - 35 ℃
	Storage Temperature	-15 - 45 ℃
	Operation Humidity	20 - 80 %RH (No Condensation)
	Storage Humidity	<=80 %RH